

FASTBIND HOT MELT TYPE 10.0

- Name:** Fastbind Hot Melt Type 10.0
- Description:** Hot melt adhesive for book binding application.
- Excellent adhesion to a variety of papers and materials and suitable for difficult-to bond papers. Good temperature resistance and spine flexibility. For soft and hard cover bindings.
- Optimal glue for Fastbind perfect binding machines, Secura, Elite, Elite XT, Optima, Pureva XT, EVA XT, Pureva Neo, Pureva SMART.
- Remarks:** **Does not mix with other glue types.** For best binding result, drain and flush pot with Type 10.0 before use.
- If the glue container was previously filled with another adhesive, the container must be completely emptied before using FASTBIND Hotmelt Type 10.0.
- For an optimal binding result, we also recommend 3 to 5 more maculature bindings or multiple spreading on a cardboard after filling the FASTBIND Hotmelt Type 10.0 to make sure that no more mixed adhesive is used.
- Appearance:** Neutral, translucent white
Granule size approx. 20x40x10(h) mm
Solid in room temperature
- Temperature:** Material is applied hot.
Recommended application temperature +160 C ... +175 C.
- Packing:** Available in 12 kg boxes. Full pallet 480 kg (40 boxes)
- Storage:** Store in original unopened packaging. Protect from sun, dust, moisture and high temperatures in clean and dry conditions. Shelf life 2 years from the date of manufacture.
- Safety & Disposal:** Refer to Materials Safety Data Sheet for details.